

ELBOW


ISO steel seamless elbows

Art. 029.0614 3D - 90° DIN 2605

Art. 029.0616 3D - 180° DIN 2605

Art. 029.0617 5D - 90° DIN 2609


Art. 029.0619 5D - 180° DIN 2609




Art. 029.0614

Execution: produced from seamless pipes St. 37.0 DIN 1629 or St.35.8/l DIN 17175 - manufacturing, execution and tolerances according to DIN 2605 3D and DIN 2609 5D - the elbows construction meets UNI/ISO 3419, NFA 99-186 and 281 requirements - smooth edges.

On request: featheredge execution - certifications according to EN 10204-DIN 50049 normatives - tests according to R.I.N.a and TUV normatives.



Sec.Art. 029.0614



Sec.Art. 029.0616

Dimensions

Ø	Thickness mm	Dima 3 ISO				Dima 5 ISO			
		r mm	Tolerances mm	90° Kg	180° Kg	r mm	Tolerances mm	90° Kg	180° Kg
17	2.0	28	±2.5	0.02	0.04	---	---	---	---
21.3	2.0	28	±2.5	0.04	0.08	43	±2.5	0.07	0.14
26.9	2.3	29	±2.5	0.06	0.12	58	±2.5	0.13	0.26
30	2.3	33	±2.5	0.10	0.20	62	±2.5	0.18	0.36
33.7	2.6	38	±2.5	0.12	0.24	73	±2.5	0.23	0.46
38	2.6	45	±2.5	0.16	0.32	83	±2.5	0.30	0.60
42.4	2.6	48	±2.5	0.19	0.38	93	±2.5	0.37	0.74
44.5	2.6	51	±2.5	0.22	0.44	98	±2.5	0.41	0.82
48.3	2.6	57	±3	0.26	0.52	108	±2.5	0.50	1.00
51	2.6	64	±3	0.31	0.62	115	±2.5	0.56	1.12
54	2.6	70	±3	0.34	0.68	120	±2.5	0.56	1.12
57	2.9	72	±3	0.44	0.88	128	±2.5	0.78	1.56
60.3	2.9	76	±3	0.49	0.98	135	±2.5	0.87	1.74
63.5	2.9	83	±3	0.56	1.12	143	±2.5	1.00	2.00
70	2.9	92	±3	0.70	1.40	160	±2.5	1.21	2.42
76.1	2.9	95	±3	0.78	1.56	175	±2.5	1.44	2.88
82.5	3.2	108	±3	1.06	2.12	190	±2.5	2.00	4.00
88.9	3.2	114	±3	1.22	2.44	205	±2.5	2.18	4.36
101.6	3.6	134	±3	1.83	3.66	238	±2.5	3.25	6.50
108	3.6	143	±3	2.08	4.16	253	±5	3.68	7.36
114.3	3.6	152	±3	2.36	4.72	270	±5	4.17	8.34
133	4.0	181	±3	3.62	7.24	313	±5	6.25	12.50
139.7	4.0	190	±4	4.00	8.00	330	±5	6.94	13.88
159	4.5	216	±4	5.80	11.60	375	±5	10.10	20.20
168.3	4.5	229	±4	6.50	13.00	390	±10	11.10	22.20
193.7	5.6	270	±4	11.00	22.00	455	±12.5	17.90	35.80
219.1	6.3	305	±4	15.80	31.60	510	±12.5	26.50	53.00
244.5	6.3	340	±4	19.80	39.60	580	±15	33.70	67.40
273	6.3	381	±5	24.80	49.60	650	±15	42.30	84.60
323.9	7.1	457	±5	39.80	79.60	775	±17.5	67.50	135
355.6	8.0	533	±10	57.50	115	850	±20	91.60	184

