


# END CAP

## ANSI/STD welding end cap


**Art. 036.1305**

**Execution:** ANSI/STD steel (Schedule 40) - according to ANSI B 16.9 normatives.

**On request:** XS execution (Schedule 80) **Art. 036.2305.**




**G.OGRINC**  
katalog strojne  
instalacije




**Art. 036.1305**

### Dimensions

Ø	Outside diameter	H mm	STD		XS		Tolerances		
			S mm	Weight Kg	S mm	Weight Kg	Diameter outs. mm	Diameter ins. mm	H mm
1/2"	21.3	25.4	2.77	0.03	-	-			
3/4"	26.7	25.4	2.87	0.06	3.91	0.08			
1"	33.4	38.1	3.38	0.10	4.55	0.14	+1.6	±0.8	±3.2
1L"	42.2	38.1	3.56	0.14	4.85	0.18	-0.8		
1"	48.3	38.1	3.68	0.16	5.08	0.23			
2"	60.3	38.1	3.91	0.27	5.54	0.32			
2"	73.0	38.1	5.16	0.41	7.01	0.45			
3"	88.9	50.8	5.49	0.65	7.62	0.82	±1.6	±1.6	—
4"	114.3	63.5	6.02	1.15	8.56	1.54			
5"	141.3	76.2	6.55	1.90	9.52	2.59	+2.4		
6"	168.3	88.9	7.11	2.92	10.97	4.10	-1.6		
8"	219.1	101.6	8.18	5.07	12.70	7.3			
10"	273	127	9.27	9.10	12.70	12			
12"	323.9	152	9.52	13.6	12.70	17			
14"	355.6	165	9.52	14.42	12.70	19.8	+4	±3.2	±6.4
16"	406.4	178	9.52	18.86	12.70	25.89	-3.2		
18"	457.2	203	9.52	27.65	12.70	36.52			
20"	508.8	229	9.52	35.60	12.70	46.98	+6.4	±4.8	
22"	558.8	254	9.52	39	12.70	56.60	-3.2		
24"	609.6	267	9.52	46	12.70	64.60			



**Sec.Art. 036.1305**



**G.OGRINC** d.o.o.

Tel.01 361 50 44, Fax.01 361 16 00, e-pošta.gogrinc@siol.net, spleť.www.g-ogrinc.si

