



**Art. 008.2253 NP 6 UNI 2253/67**

**Art. 008.2254 NP 16 UNI 2254/67**

**Execution:** ASTM A105 steel - completely turned and lined on the contact surface - pipe screw according to UNI 338 and drilled as table

**Diameters:** 3/8" ÷ 6"

**On request:** raised face according to UNI 2229.

### Dimensions and weights

Diameter	Outside diameter D	Thickness b	Center line a	Holes n°	Diameter f	h	m	Pipe nominal diameter D	Approx. weight Kg.
<b>UNI 2253/67 NP 6</b>									
3/8"	75	12	50	4	11	20	25	10	0.390
1/2"	80	12	55	4	11	20	30	15	0.430
3/4"	90	14	65	4	11	24	40	20	0.660
1"	100	14	75	4	11	24	50	25	0.820
1L"	120	14	90	4	14	26	60	32	1.170
1"	130	14	100	4	14	26	70	40	1.400
2"	140	14	110	4	14	28	80	50	1.590
2"	160	14	130	4	14	32	100	65	2.170
3"	190	16	150	4	18	34	110	80	3.200
4"	210	16	170	4	18	38	130	100	3.590
5"	240	18	200	8	18	40	160	125	4.940
6"	265	18	225	8	18	44	185	150	5.830
<b>UNI 2254/67 NP 16</b>									
3/8"	90	14	60	4	14	20	30	10	0.630
1/2"	95	14	65	4	14	20	35	15	0.700
3/4"	105	16	75	4	14	24	45	20	1.010
1"	115	16	85	4	14	24	52	25	1.210
1L"	140	16	100	4	18	26	60	32	1.760
1"	150	16	110	4	18	26	70	40	2.040
2"	165	18	125	4	18	28	85	50	2.850
2"	185	18	145	4	18	32	105	65	3.530
3"	200	20	160	8	18	34	118	80	4.240
4"	220	20	180	8	18	38	140	100	4.900
5"	250	22	210	8	18	40	168	125	6.630
6"	285	22	240	8	22	44	195	150	8.490